

Kodak easysshare camera touch



M5370

Specifications

Sensor type	1/2.3-type CCD
CCD total pixels	16.4 MP (4700 x 3498)
Effective pixels	16 MP (4624 x 3472)
Zoom	SCHNEIDER-KREUZNACH 5X optical zoom Lens, 5X digital zoom
Focal length	28 - 140 mm (35 mm equivalent)
Lens protection	Built-in auto lens cover
Shutter speed	Smart Capture mode: 1/8 - 1/1600 sec. Long time exposure mode: 8 - 1/2 sec.
Display	7.6 cm (3.0-type), 230K high-resolution capacitive LCD touchscreen with auto brightness control
Storage	64 MB ² internal memory, micro SD/SDHC memory card slot
Focus system	TTL-AF multi-zone, center-zone, face priority
Focus range	Smart Capture mode: [wide] 0.5 m (1.6') - infinity, [tele] 1.5 m (4.9') - infinity; close up mode: [wide] 0.05 - 0.8 m (1.9" - 2.6'), [tele] 1.0 - 1.8 m (3.3' - 5.9')
Auto focus control	Continuous, single
Face detection	Yes
Face Recognition	Yes
ISO sensitivity	Auto, ISO 64, 100, 200, 400, 800, 1600
Exposure compensation	+/-2.0 EV with 1/3 EV steps
AF/AE lock	When shutter button is depressed 1/2-way
White balance	Smart Capture, scene modes, auto; P mode: selectable auto, daylight, tungsten, fluorescent, open shade
Flash range	[wide] 0.5 - 3.2 m (1.6' - 10.5'), [tele] 1.0 - 2.2 m (3.3' - 7.2') at ISO 400 in auto
Flash modes	Auto, fill, red-eye reduction, off
Shooting modes (still)	
Smart Capture mode	Yes
Touch Shutter mode	Yes (AE/AF process included)
Film effects	KODACOLOR, KODACHROME, EKTACHROME, T-MAX, TRI-X, Sepia
Photo booth	Yes
Scene modes	Program AE (P), portrait, sport, landscape, close-up, sunset, backlight, candlelight, children, bright, fireworks, self-portrait, night portrait, night landscape, blur reduction, high ISO, panorama, long time exposure, text
Self-timer/burst modes	Self-timer (2 sec., 10 sec., 2 shots); burst: maximum 3 shots
Still capture/review	
Still format	JPEG/EXIF v2.3
Picture size (recorded pixels)	16 MP (4:3) 4608 x 3456 14 MP (3:2) 4608 x 3072 12 MP (16:9) 4608 x 2592 6 MP (4:3) 2880 x 2160 3 MP (4:3) 2048 x 1536
Color modes	Vivid, full, basic, black & white, and sepia
Sharpness	Sharp, normal (default), soft
Orientation sensor	Yes
Date stamp	Yes
Review	Viewing: Face Recognition (date, face), single-up, multi-up/ thumbnails, magnify, fast scroll, multi-select, delete, undo- delete, slide show; tagging: Share, print, e-mail, keyword, keyboard input; photo effects
Editing	Crop, KODAK PERFECT TOUCH Technology (if not applied during capture), auto move, film effects
Video capture/review	
File format (video)	H.264, ACC, MP4 with audio recording during capture
Video size	720p (16:9) 1280 x 720 @ 30 fps; VGA (4:3), 640 x 480 @ 30 fps
AF/AE during video	Continuous AE
Zoom during video	Digital zoom

Microphone	Yes, monaural
Speaker	Yes, monaural
Recording limit	VGA: <4GB; HD: <4GB or <29 min.
Review	FF, rewind, pause, by frame, volume control
Editing	Make picture, trim, 9-up action print, auto move
Share	
Share menu	FACEBOOK, FLICKR, KODAK Gallery, ORKUT, YOUTUBE, TWITTER, YANDEX, KAIXIN sites ³ , e-mail
Features	Pictures, videos, multiple selections, multiple destinations

Customization

Custom settings	Share button settings, LCD brightness, sound volume, people tag, slide show, reset all camera settings, computer connection, safe mode, date & time, video out, language, format, about, Kodak camera software
-----------------	--

Physical specifications

I/O interface	A/V output (NTSC or PAL selectable), digital USB 2.0 high speed
Power	In-camera charging, KODAK Li-Ion Rechargeable Digital Camera Battery — KLIC-7006
Dedicated buttons	Power, shutter, zoom, review, video, Share
Tripod mount	1/4" standard
Dimensions	94.0 mm (W) x 57.3 mm (H) x 19.3 mm (D) (3.9" x 2.3" x 0.8")
Weight	137 g (4.8 oz.) with battery and card
Compatibility	
Direct print	PICTBRIDGE enabled
Software	KODAK Share Button App; works with KODAK EASYSHARE Software

Service and support

Warranty	One year
----------	----------

Minimum system requirements

WINDOWS	WINDOWS XP SP2, VISTA, WINDOWS 7 or later, INTERNET EXPLORER 6.0 or higher
MACINTOSH	MACINTOSH 10.4 or higher

Minimum hardware requirements

PENTIUM 4 1.4 GHz processor or higher (PENTIUM 4 2.8 GHz processor or higher for HD video), 1 GB RAM (64 MB video RAM for HD video), 1024 x 768 display resolution, 300 MB available hard drive space, USB v1.1 or higher

Package contents

KODAK EASYSHARE TOUCH Camera, M5370; KODAK Li-Ion Rechargeable Digital Camera Battery — KLIC-7006; AC adapter for in-camera battery charging; USB cable; wrist strap; User Guide

Ordering information

KODAK EASYSHARE TOUCH Camera, M5370	
Silver	CAT 884 6206
Blue	CAT 183 7897

Recommended accessories

KODAK Hard Case/Black	CAT 197 2736
KODAK Essential Screen Protectors	CAT 176 6922
KODAK Essential Clip Case/Twist Ultra Compact	CAT 154 9294
KODAK Gripping Tripod/SM Grey	CAT 128 8703
KODAK Essential Screen Protectors	CAT 176 6922
KODAK USB 5 Pin Cable	CAT 152 6979
KODAK Essential Universal Li-Ion Battery Charger UC-200	CAT 863 9944
KODAK Essentials Li-Ion Batt KLIC 7004	CAT 131 0564
KODAK MicroSD Mobile Memory Card — 8 GB	CAT 843 4979
(also 4, 16, & 32 GB compatible)	

¹All KODAK Still Cameras manufactured in 2010 or later.
²64 MB internal memory/18 MB available for video and picture storage (1 MB equals 1 million bytes).
³Sharing sites vary by region.



Just press to Impress.



For more information on the KODAK EASYSHARE M5370 Camera, visit www.kodak.com/go/sharebutton

